

**Listing of Claims:**

1. (Currently amended) An X-ray unit comprising at least a first arrangement (2) for the contactless and X-ray-free measurement of first data of an object (1), a second arrangement (4) for measuring X-ray data of the object (1) using X-rays, and a control unit (3) that is provided for controlling the second arrangement (4) as a function of the first data, wherein at least one of intensity and mean energy of the X-rays is controlled by the control unit (3) based at least in part on the first data.
2. (Currently amended) An X-ray unit as claimed in claim 1, ~~wherein~~characterized in that the first arrangement (2) is equipped to use light or sound to measure the first data the first arrangement is stationary with respect to the object, and wherein the second arrangement rotates with respect to the object.
3. (Currently amended) An X-ray unit as claimed in claim 1, ~~wherein~~characterized in that the first arrangement (2) comprises a transmitter (2') for transmitting light or sound and a receiver (2'') for receiving the reflected light or sound.
4. (Currently amended) An X-ray unit according to claim 1, ~~wherein~~characterized in that the first data are geometry data of the object (1).
5. (Currently amended) An X-ray unit comprising at least a first arrangement (2) for the contactless and X-ray-free measurement of first data of an object (1), a second arrangement (4) for measuring X-ray data of the object (1) using X-rays, and a control unit (3) that is provided for controlling the second arrangement (4) as a function of the first data, as claimed in claim 1, characterized in that~~wherein~~the first arrangement (2) measures the first data by means of triangulation, stereoscopy or transit time determination.

6. (Currently amended) An X-ray unit as claimed in claim 1, ~~wherein characterized in~~  
~~that the first arrangement (2) has a measuring unit (2.1) that is intended to rotate~~ around  
the object (1).

7. (Currently amended) An X-ray unit as claimed in claim ~~1~~5, ~~wherein characterized in~~  
~~that the first arrangement (2) comprises a plurality of spatially stationary measuring units~~  
(2.1, 2.2, 2.3).

8. (Currently amended) An X-ray unit as claimed in claim ~~1~~5, ~~wherein characterized in~~  
~~that the second arrangement (4) has an X-ray source (2') that is intended to rotate~~ around  
the object (1), ~~and~~ and wherein at least one of ~~in that the intensity and/or mean energy of~~  
~~the X-rays are/is controlled by the control unit (3) based at least in part on the first data.~~

9. (Currently amended) An X-ray unit as claimed in claim 1, ~~wherein characterized in~~  
~~that the X-ray unit comprises a processor unit (10) that is intended to convert data (D)~~  
measured in the first arrangement (2) into geometry data (D').

10. (Currently amended) A method of measuring X-ray data of an object (1) that  
comprises the following steps:

~~measuring~~ measurement of first data of the object (1) by means of a contactless and X-  
ray-free method that is stationary with respect to the object,

~~starting of the measurement of the~~ obtaining X-ray data of the object (1) by means  
of X-rays from an emitter that rotates with respect to the object, and

controlling the measurement of the X-ray data as a function of the first data.

11. (Original) A method according to claim 10 in which the step of measuring the first  
data is accomplished by means of sound or light, whereby as an intermediate step in the  
measurement step the light or sound is reflected by a reflection-optimizing means (1') that  
is provided on the object (1).

12. (New) The method of claim 10, further comprising determining the first data by triangulation.

13. (New) The method of claim 10, further comprising controlling at least one of an intensity or mean energy of the X-rays based at least in part on the first data.

14. (New) The method of claim 10, further comprising determining a geometry of the object from the first data.

15. (New) The method of claim 10, further comprising determining the geometry of the object based on the first data and a geometry of a support structure for the object.